

Secure
your World
in Every
Sight



AHD CCTV Cameras

2.4MP Dome IR (Eco)

HDC-ECO-2.4-ID



- 1/3", 2.4 Megapixel CMOS Sensor
- Resolution: 1920(H) x 1080(V)
- Lens: 3.6mm (Fixed)
- UTC 4-in-1
- Min. Illumination: 0.01 Lux/F1.2 (IR On)
- Up to 15-20m IR Distance, 18 Smart IR LEDs
- 3D Noise Reduction, Lightning Protection, Anti-Fog Function

2.4MP Bullet IR (Eco)

HDC-ECO-2.4-OD



- 1/3", 2.4 Megapixel CMOS Sensor
- Resolution: 1920(H) x 1080(V)
- Lens: 3.6/6mm (Fixed)
- UTC 4-in-1
- Min. Illumination: 0.01 Lux/F1.2 (IR On)
- Up to 20m IR Distance, 18 Smart IR LEDs
- 3D Noise Reduction, Lightning Protection, Anti-Fog Function

2.4MP Dome IR (Reg.)

HDC-SONY-2.4-ID



- 1/3", 2.4 Megapixel CMOS Sensor
- Resolution: 1920(H) x 1080(V)
- Lens: 3.6mm (Fixed)
- UTC 4-in-1
- Min. Illumination: 0.01 Lux/F1.2 (IR On)
- Up to 20m IR Distance, 3 Array LEDs
- 3D Noise Reduction, Lightning Protection, Anti-Fog Function

2.4MP Bullet IR (Reg.)

HDC-SONY-2.4-OD-MT



- 1/3", 2.4 Megapixel CMOS Sensor
- Resolution: 1920(H) x 1080(V)
- Lens: 3.6/6mm (Fixed)
- UTC 4-in-1
- Min. Illumination: 0.01 Lux/F1.2 (IR On)
- Up to 30m IR Distance, 18 Smart IR LEDs
- 3D Noise Reduction, Lightning Protection, Anti-Fog Function
- Metal Body IP-66

TURBO SERIES CAMERAS

2.4MP Bullet IR (Long Distance)

HDC-CORE-2.4-OD-L6/L8/L12



- 1/3", 2.4 Megapixel CMOS Sensor
- Resolution: 1920(H) x 1080(V)
- Lens: 6mm, 8mm, 12mm (Fixed)
- UTC 4-in-1
- Min. Illumination: 0.01 Lux/F1.2 (IR On)
- Up to 40/60/80m IR Distance, 2-ARRAY/4-ARRAY IR LEDs
- 3D Noise Reduction, Lightning Protection, Anti-Fog Function

5MP Dome IR (Turbo)

HDC-TURBO-5MP-ID



- 1/3", 5.0 Megapixel CMOS Sensor
- Lens: 3.6mm (Fixed)
- Resolution: 2592 x 1944
- Min. Illumination: 0.01 Lux/F1.2 (IR On)
- Up to 20m IR Distance, 18 Smart IR LEDs
- 3D Noise Reduction, Lightning Protection, Anti-Fog Function
- UTC 4-in-1

5MP Bullet IR (Turbo)

HDC-TURBO-5MP-OD METAL



- 1/3", 5.0 Megapixel CMOS Sensor
- Lens: 3.6mm/6mm (Fixed)
- Resolution: 2592 x 1944
- Min. Illumination: 0.01 Lux/F1.2 (IR On)
- Up to 30m IR Distance, 18 Smart IR LEDs
- 3D Noise Reduction, Lightning Protection, Anti-Fog Function
- Outdoor: Weather-proof Big Metal Body

5MP Bullet IR (Turbo Long Distance)

HDC-TURBO-5MP-OD-L6/L8/L12



- 1/3", 5.0 Megapixel CMOS Sensor
- Lens: 6mm, 8mm, 12mm Fixed Lens
- Resolution: 2592 x 1944
- Min. Illumination: 0.01 Lux/F1.2 (IR On)
- Up to 40/60/80m IR Distance, 2-ARRAY/4-ARRAY IR LEDs
- 3D Noise Reduction, Lightning Protection, Anti-Fog Function
- UTC 4-in-1
- Outdoor: Big Metal Body

Full Colour AHD Cameras

2.4MP Dome STARLIGHT

HDC-AHD-PHD-STL-2.4-ID



- STARLIGHT 1/3", 2.4 Megapixel CMOS Sensor
- Lens: 3.6/4mm (Fixed)
- Resolution: 1920(H) x 1080(V)
- Min. Illumination: 0.01 Lux/F1.2 (IR On)
- Up to 20 to 30m IR Distance, Array Smart LEDs
- 24/7 Full Color Vision

2.4MP Bullet STARLIGHT

HDC-AHD-PHD-STL-2.4-OD (Plastic)



- STARLIGHT 1/3", 2.4 Megapixel CMOS Sensor
- Lens: 3.6/4mm (Fixed)
- Resolution: 1920(H) x 1080(V)
- Min. Illumination: 0.01 Lux/F1.2 (IR On)
- Up to 30m IR Distance, Array Smart LEDs
- 24/7 Full Color Vision

2.4MP Bullet STARLIGHT

HDC-AHD-PHD-STL-2.4-OD (Metal)



- STARLIGHT 1/3", 2.4 Megapixel CMOS Sensor
- Lens: 3.6/4mm (Fixed)
- Resolution: 1920(H) x 1080(V)
- Min. Illumination: 0.01 Lux/F1.2 (IR On)
- Up to 30m IR Distance, Array Smart LEDs
- 24/7 Full Color Vision
- Outdoor: Weather-proof, Ip66

2.4MP Dome STARLIGHT

HDC-AHD-STL-W2.4-ID



- STARLIGHT 1/3", 2.4 Megapixel CMOS Sensor
- Lens: 3.6/4mm (Fixed)
- Resolution: 1920(H) x 1080(V)
- Min. Illumination: 0.01 Lux/F1.2 (IR On)
- Up to 20 to 30m IR Distance, Array Smart LEDs
- 24/7 Full Color Vision

2.4MP Bullet STARLIGHT

HDC-AHD-STL-W2.4-OD (Metal)



- STARLIGHT 1/3", 2.4 Megapixel CMOS Sensor
- Lens: 4mm (Fixed)
- Resolution: 1920(H) x 1080(V)
- Min. Illumination: 0.01 Lux/F1.2 (IR On)
- Up to 30m IR Distance, Array Smart LEDs
- 24/7 Full Color Vision
- Outdoor: Weather-proof, Ip66

5 MP Dome FULL COLOR

HDC-AHD-STL-5MP-ID (With Audio)



- STARLIGHT 1/3", 5 Megapixel CMOS Sensor
- Lens: 4 mm (Fixed)
- Resolution: 2592 x 1944
- Min. Illumination: 0.01 Lux/F1.2 (IR On)
- Up to 25m IR Distance, Array Smart LEDs
- 24/7 Full Color Vision

5MP Bullet FULL COLOR

HDC-AHD-STL-5MP-OD (With Audio)



- STARLIGHT 1/3", 5 Megapixel CMOS Sensor
- Lens: 4/6mm (Fixed)
- Resolution: 2592 x 1944
- Min. Illumination: 0.01 Lux/F1.2 (IR On)
- Up to 30/40/50m IR Distance, Array Smart LEDs
- 24/7 Full Color Vision
- Outdoor: Weather-proof, Ip66

5MP Bullet (Long Distance)

HDC-AHD-STL-5MP-OD-L6/L8/L12



- STARLIGHT 1/3", 5 Megapixel CMOS Sensor
- Lens: 6mm/8mm/12mm (Fixed)
- Resolution: 2592 x 1944
- Min. Illumination: 0.01 Lux/F1.2 (IR On)
- Up to 40/60/80m IR Distance, Array Smart LEDs
- 24/7 Full Color Vision
- Outdoor: Weather-proof

IP Cameras

4MP Dome IP (With PoE & Audio)

HDC-IP-4MP-265-ID-4K



- 1/3", 4 Megapixel CMOS Image Sensor
- 4.0mp H/Resolution 2560(H) x 1440(V)
- 3.6mm/4mm Fixed Lens (6mm opt.)
- Maximum 25/30 fps
- Support: LAN Wire
- Smart Array Range Up to 20m to 30m
- H.264/H.265 Dual Stream Enc.
- 3D DNR, AGC, AWB, BLC Supported Anti-Fog Function

4MP Bullet IP (With PoE & Audio)

HDC-IP-4MP-265-OD-4K



- 1/3", 4 Megapixel CMOS Image Sensor
- 4.0mp H/Resolution 2560(H) x 1440(V)
- 3.6mm/4mm Fixed Lens (6mm opt.)
- Maximum 25/30 fps
- Support: LAN Wire
- Smart Array Range Up to 20m to 30m
- H.264/H.265 Dual Stream Enc.
- 3D DNR, AGC, AWB, BLC Supported Anti-Fog Function

4MP Bullet IP (With PoE & Audio)

HDC-IP-4MP-265-OD-4K-L6/L8/L12



- 1/3", 4 Megapixel CMOS Sensor
- Lens: 6mm/8mm/12mm (Fixed)
- Resolution: 2560(H) x 1440(V)
- Maximum 25/30 fps
- Support: LAN Wire
- Smart Array Range Up to 40/60/80m
- H.264/H.265 Dual Stream Enc.
- 3D DNR, AGC, AWB, BLC Supported

5MP Dome IP (With PoE & Audio)

HDC-IP-5MP-265-ID-4K



- 1/3", 5 Megapixel CMOS Image Sensor
- Resolution: 2592 x 1944
- 3.6mm/4mm Fixed Lens (6mm opt.)
- Maximum 25/30 fps
- Support: LAN Wire
- Smart Array Range Up to 20m to 25m
- H.264/H.265 Dual Stream Enc.
- 3D DNR, AGC, AWB, BLC Supported

5MP Bullet IP (With PoE & Audio)

HDC-IP-5MP-265-OD-4K



- 1/3", 5 Megapixel CMOS Image Sensor
- Resolution: 2592 x 1944
- 3.6mm/4mm Fixed Lens (6mm opt.)
- Maximum 25/30 fps
- Support: LAN Wire
- Smart Array Range Up to 25m to 30m
- H.264/H.265 Dual Stream Enc.
- 3D DNR, AGC, AWB, BLC Supported

5MP Bullet IP (With PoE & Audio)

HDC-IP-5MP-265-OD-4K L6/L8/L12



- 1/3", 5 Megapixel CMOS Sensor
- Lens: 6mm/8mm/12mm (Fixed)
- Resolution: 2592 x 1944
- Maximum 25/30 fps
- Support: LAN Wire
- Smart Array Range Up to 40/60/80m
- H.264/H.265 Dual Stream Enc.
- 3D DNR, AGC, AWB, BLC Supported

Full Colour IP Cameras

4MP Starlight Dome IP (With PoE & Audio)

HDC-IP-4MP-STL-ID-4K



- 1/3", 4 Megapixel CMOS Image Sensor
- 4.0mp H/Resolution 2560(H) x 1440(V)
- 3.6mm Fixed Lens (6mm opt.)
- Maximum 25/30 fps
- Support: LAN Wire
- Smart Array Range Up to 20m to 25m
- H.265/H.265 Dual Stream Enc.
- 24/7 Full Color Vision
- 3D DNR, AGC, AWB, BLC Supported

4MP Starlight Bullet IP (With PoE & Audio)

HDC-IP-4MP-STL-ID-4K



- 1/3", 4 Megapixel CMOS Image Sensor
- 4.0mp H/Resolution 2560(H) x 1440(V)
- 3.6mm/4mm Fixed Lens (6mm opt.)
- Maximum 25/30 fps
- Support: LAN Wire
- Smart Array Range Up to 25m to 30m
- H.264/H.265 Dual Stream Enc.
- 24/7 Full Color Vision
- 3D DNR, AGC, AWB, BLC Supported

4MP Starlight Bullet IP (With PoE & Audio)

HDC-IP-4MP-STL-OD-4K-L6/L8/L12



- 1/3", 4 Megapixel CMOS Image Sensor
- Lens: 6mm/8mm/12mm (Fixed)
- Resolution: 2560(H) x 1440(V)
- Maximum 25/30 fps
- Support: LAN Wire
- Smart Array Range Up to 40/60/80m
- H.264/H.265 Dual Stream Enc.
- 24/7 Full Color Vision
- 3D DNR, AGC, AWB, BLC Supported

5MP Starlight Dome IP (With PoE & Audio)

HDC-IP-5MP-STL-ID-4K



- 1/3", 5 Megapixel CMOS Image Sensor
- Resolution: 2592 x 1944
- 3.6mm Fixed Lens (6mm opt.)
- Maximum 25/30 fps
- Support: LAN Wire
- Smart Array Range Up to 20m to 30m
- H.264/H.265 Dual Stream Enc.
- 24/7 Full Color Vision
- 3D DNR, AGC, AWB, BLC Supported
- Metal Body

5MP Starlight Bullet IP (With PoE & Audio)

HDC-IP-5MP-STL-OD-4K



- 1/3", 5 Megapixel CMOS Image Sensor
- Resolution: 2592 x 1944
- 3.6mm/4mm Fixed Lens (6mm opt.)
- Maximum 25/30 fps
- Support: LAN Wire
- Smart Array Range Up to 25m to 30m
- H.264/H.265 Dual Stream Enc.
- 24/7 Full Color Vision
- 3D DNR, AGC, AWB, BLC Supported
- Metal Body, IP 66

5MP Starlight Bullet IP (With PoE & Audio)

HDC-IP-5MP-STL-OD-4K-L6/L8/L12



- 1/3", 5 Megapixel CMOS Image Sensor
- Lens: 6mm/8mm/12mm (Fixed)
- Resolution: 2592 x 1944
- Maximum 25/30 fps
- Support: LAN Wire
- Smart Array Range Up to 40/60/80m
- H.264/H.265 Dual Stream Enc.
- 24/7 Full Color Vision
- 3D DNR, AGC, AWB, BLC Supported

4G Cameras

IP 4G WiFi Dome

HDC-4G-D-3MP-IP



- Array Dome 3MP
- Dual Light
- Built in High-Sensitivity Mic & Speaker
- Two Way Communication
- Image Sensor – ½.7” CMOS
- Resolution 2304 x 1296
- Lens – 4MM Fixed Lens

IP 4G WiFi Bullet

HDC-4G-B-3MP-IP



- Array Bullet 3MP
- Dual Light
- Built in High-Sensitivity
- Mic & Speaker
- Two Way Communication
- Image Sensor – ½.7” CMOS
- Resolution 2304 x 1296
- Lens – 3.6MM Fixed Lens

Fish Eye Cameras

AHD Fish Eye

HDC-AHD-FE-200



- High Definition 2MP Resolution
- 1/3” Progressive Image Sensor
- 2 Megapixel 1.3mm Lens
- 3 IR Array LED For Superior Night Vision
- IRC For True Day And Night Vision
- Lux F (1.2,50 IRE, AGC ON)
- Defog, DWDR, 2D/3DNR
- IR Range – Up to 25m
- 360° Panoramic View

Varifocal Cameras

5MP Bullet IP (Varifocal)

HDC-IP-5MP-VAR-OD



- 5MP Varifocal IP Camera
- H.265/H.264 High profile
- 36 Pieces IR Leds
- 30-80 Meters Infrared Night Vision
- 2.8-12mm 5.0 Megapixel Manual Varifocal Lens
- Standard ONVIF Protocol
- High quality progressive scanning CMOS

PTZ

30X IP PTZ

HDC-IP-5MP-PTZ



- Support P2P function, H.265
- 5MP, 30X Optical Zoom
- 6” Half Metal Body Construction, Ip66
- ONVIF: Compatible
- Intelligent IR illumination & power consumption is variable, dependant the zoom factor

DVR Series

4 Channel T Series DVR

HDC-4100-T-1080P



- 4CH TVI / CVI / AHD video input
- 4CH 1080P lite / 720P / WD1 recording
- 4CH 1080P lite / 720P / 720P lite / WD1 recording
- 4CH DVRs support 1 / 1 CH IPC 1080P 960P / 720P recording
- Adopt standard H.265+High Profile Compression

8 Channel T Series DVR

HDC-8100-T-1080P



- 8CH TVI / CVI / AHD video input
- 8CH 1080P lite / 720P / WD1 recording
- 8CH 1080P lite / 720P / 720P lite / WD1 recording
- 8CH DVRs support 1 / 1 CH IPC 1080P 960P / 720P recording
- Adopt standard H.265+High Profile Compression

16 Channel T Series DVR

HDC-1600-T-1080P



- 16CH TVI / CVI / AHD video input
- 16CH 1080P lite / 720P / WD1 recording
- 16CH 1080P lite / 720P / 720P lite / WD1 recording
- 16CH DVRs support 1 / 1 CH IPC 1080P 960P / 720P recording
- Adopt standard H.265+High Profile Compression

4 Channel D Series DVR

HDC-4CH-5D-H265



- Operation: Embedded Linux Operating System
- Resolution: 4 Ch (5MP Lite)
- Video Compression: H.265
- Video Output: 1-VGA, 1-HDMI
- Audio Input: 4CH Coaxial Support
- Playback Quality: 5MP X 4 Ch
- Image Display: 1/4
- Video Speed: 5MP, 22 fps
- Supports: CVBS, AHD, IP, CVI, TVI

8 Channel D Series DVR

HDC-8CH-5D-H265



- Operation: Embedded Linux Operating System
- Resolution: 8 Ch (5MP Lite)
- Video Compression: H.265
- Video Output: 1-VGA, 1-HDMI
- Audio Input: 8CH Coaxial Support
- Playback Quality: 5MP X 8Ch
- Image Display: 1/8
- Video Speed: 5MP, 22 fps
- Supports: CVBS, AHD, IP, CVI, TVI

16 Channel D Series DVR

HDC-16CH-5D-H265



- Operation: Embedded Linux Operating System
- Resolution: 16 Ch (5MP Lite)
- Video Compression: H.265
- Video Output: 1-VGA, 1-HDMI
- Audio Input: 16CH Coaxial Support
- Playback Quality: 5MP X 16 Ch
- Image Display: 1/16
- Video Speed: 5MP, 22 fps
- Supports: CVBS, AHD, IP, CVI, TVI

32 Channel D Series DVR

HDC-32CH-5D-H265



- Operation: Embedded Linux Operating System
- Resolution: 32 Ch (5MP Lite)
- Video Compression: H.265
- Video Output: 1-VGA, 1-HDMI
- Audio Input: 32CH Coaxial Support
- Playback Quality: 5MP X 16Ch
- Image Display: 1/32
- Video Speed: 5MP, 22 fps
- Supports: CVBS, AHD, IP, CVI, TVI

NVR Series

10 Channel NVR

HDC-NVR-10Ch-H265-4K



- Recording: 25 fps
- Support Camera: 1080p, 4MP/5MP & 8MP
- Communication: LAN+USB
- Playback: 10 Ch
- Motion Recording: Yes
- Output: VGA+HDMI
- Audio: 8 Ch
- USB Port: 2 Port

16 Channel NVR

HDC-NVR-16Ch-H265-4K



- Recording: 25 fps
- Support Camera: 1080p, 4MP/5MP & 8MP
- Communication: LAN+USB
- Playback: 16 Ch
- Motion Recording: Yes
- Output: VGA+HDMI
- Audio: 16 Ch
- USB Port: 2 Port

32 Channel NVR

HDC-NVR-32Ch-H265-4K



- Recording: 25 fps
- Support Camera: 1080p, 4MP/5MP & 8MP
- Communication: LAN+USB
- Playback: 32 Ch
- Motion Recording: Yes
- Output: VGA+HDMI
- Audio: 32 Ch
- USB Port: 2 Port

64 Channel NVR

HDC-NVR-64Ch-H265-4K



- Recording: 25 fps
- Support Camera: 1080p, 4MP/5MP & 8MP
- Communication: LAN+USB
- Playback: 64 Ch
- Motion Recording: Yes
- Output: VGA+HDMI
- Audio: 64 Ch
- USB Port: 2 Port

NVR Series
4 Channel NVR
HDC-N-4-T-NVR


- Support 8MP/5MP/4MP/3MP/1080P/ 960P/720P/960H/ DI/CIF IP video input
- H.265S/H.265+/H.265/H.264 coding
- Intuitive and user-friendly Graphic User Interface (GUI)
- Windows style operation by mouse
- Playback : 4CH simultaneous playback
- Search : time slice, time, event, tag, smart search
- Support multiple VCA (Video Content Analytics) events
- HDD Support Upto 8TB

8 Channel NVR
HDC-N-8-T-NVR


- Support 8MP/5MP/4MP/3MP/1080P/ 960P/720P/960H/ DI/CIF IP video input
- H.265S/H.265+/H.265/H.264 coding
- Intuitive and user-friendly Graphic User Interface (GUI)
- Windows style operation by mouse
- Playback : 4/8CH simultaneous playback
- Search : time slice, time, event, tag, smart search
- Support multiple VCA (Video Content Analytics) events
- HDD Support Upto 8TB

16 Channel NVR
HDC-N-16-T-NVR


- Support 8MP/5MP/4MP/3MP/1080P/ 960P/720P/960H/ DI/CIF IP video input
- H.265S/H.265+/H.265/H.264 coding
- Intuitive and user-friendly Graphic User Interface (GUI)
- Windows style operation by mouse
- Playback : 8/16CH simultaneous playback
- Search : time slice, time, event, tag, smart search
- Support multiple VCA (Video Content Analytics) events
- HDD Support Upto 8TB

Power Supply
4 Channel Single
HDC-WOS-004


- Input Voltage: AC 100 - 264V 50 /60Hz
- Output Voltage: 12V DC, 4A
- Voltage: Adjustment Range: ±20%
- Output Voltage Type - DC Current Shell
- Material: Metal Case / Aluminum Base
- Color: Black

8 Channel Single
HDC-WOS-008


- Input Voltage: AC 100 - 264V 50 /60Hz
- Output Voltage: 12V DC, 8A
- Voltage: Adjustment Range: ±20%
- Output Voltage Type - DC Current Shell
- Material: Metal Case / Aluminum Base
- Color: Black

16 Channel Metal
HDC-WOS-16-MT


- Input Voltage: AC 100 - 264V 50 /60Hz
- Output Voltage: 12V DC, 16A
- Voltage: Adjustment Range: ±20%
- Output Voltage Type - DC Current Shell
- Material: Metal Case / Aluminum Base
- Color: White

4 Channel Multi
HDC-400


- BIS Approved
- Highly Integrated SMPS Switcher I.C. Design
- Stabilized Output Low Interference
- Surge Protection, Over Temperature Protection
- Over Current, Over Voltage & Over Load Protection
- High-efficiency, low energy Consumption
- Individual output with Resettable Fuse

8 Channel Multi
HDC-800


- BIS Approved
- Highly Integrated SMPS Switcher I.C. Design
- Stabilized Output Low Interference
- Surge Protection, Over Temperature Protection
- Over Current, Over Voltage & Over Load Protection
- High-efficiency, low energy Consumption
- Individual output with Resettable Fuse

16 Channel Multi
HDC-1600


- BIS Approved
- Highly Integrated SMPS Switcher I.C. Design
- Stabilized Output Low Interference
- Surge Protection, Over Temperature Protection
- Over Current, Over Voltage & Over Load Protection
- High-efficiency, low energy Consumption
- Individual output with Resettable Fuse

PoE Switches
4 Channel (Normal)
HDC-POE-0402-IP


- 4 Ch POE + 2 Ch Uplink
- 4*10/100 Base-TX Ethernet Ports (Poe Ports)
- 2*10/100 For Uplink Ports
- IEEE 802.3Af/At
- 1.6 G Bandwidth, 75W Max Power Single Port
- Shell Thickness Only 32mm
- RJ 45 Port Support POE+ Supply
- Plug and Play

8 Channel (Normal)
HDC-POE-0802-IP


- 8 Ch POE + 2 Ch Uplink
- 8*10/100 Base-TX Ethernet Ports (Poe Ports)
- 2*10/100 For Uplink Ports
- IEEE 802.3Af/At
- 2 G Bandwidth, 120W Max Power Single Port
- RJ 45 Port Support POE+ Supply
- Plug and Play

8 Channel (Uplink Giga)
HDC-8+2-UPLINK-GIGA


- 8 Ch POE + 2 Ch Giga Uplink
- 8*10/100 Base-TX Ethernet Ports (Poe Ports)
- 2*10/100/1000 For Uplink Ports
- IEEE 802.3Af/At
- 20 G Bandwidth, 120W Max Power Single Port
- RJ 45 Port Support POE+ Supply
- Plug and Play

16 channel (Uplink Giga)
HDC-POE-1602-GIGA-IP


- 16 Ch POE + 2 Ch Uplink + 1 Ch SFP
- IEEE 802.3Af/At
- 16*10/100 Base-TX Ethernet Ports (Poe Ports)
- 2*10/100/1000 Uplink Port
- 20 G Bandwidth, 120W Max Power Single Port
- AC Input 100~240V
- Support VLAN, Transmission 250m
- RJ 45 Port Support POE+ Supply
- Plug and Play

24 channel (Uplink Giga)
HDC-POE-2422-GIGA-IP


- 24 Ch POE + 2 Ch Uplink Giga + 2 Ch SFP
- 24*10/100 Base-TX Ethernet Ports (Poe Ports)
- 2*10/100/1000 Uplink Ports
- IEEE 802.3Af/At
- 20 G Bandwidth, 120W Max Power Single Port
- AC Input 100~240V
- Support VLAN, Transmission 250m
- RJ 45 Port Support POE+ Supply
- Plug and Play

CCTV Cables

Coaxial Cable

HDC-2-STAR



- Single Strand 3+1 CCTV Cable with 36 Braiding
- Full Copper 60m Cable Bundle
- Video Conductor Gauge: 0.020 Inches
- Power Support 14/43

HDC-3-STAR



- 3+1 CCTV Cable
- Full Copper 70m Cable Bundle
- Video Conductor Single Strand
- 36 Braiding
- Video Conductor Gauge: 0.020 Inches
- Power Support 14/43

HDC-5-STAR



- 3+1 CCTV Cable
- Full Copper 80m Cable Bundle
- Video Conductor Single Strand
- 36 Braiding
- Video Conductor Gauge: 0.022 Inches
- Power Support 14/42

HDC-7-STAR



- 3+1 CCTV Cable Full Copper
- Video Conductor Single Strand
- 36 Braiding
- Video Conductor Gauge: 0.022 Inches
- Length: 90 Meter Bundle
- Heavy Copper
- A Grade PVC and LD
- Power Support 14/42

HDC-10-STAR



- 3+1 CCTV Full Copper Cable
- Single Strand Video Copper
- 36 Braiding
- Video Conductor Gauge: 0.024 Inches
- Length: 90 Meter Bundle
- Smart Box Packaging
- Heavy Copper
- A Grade PVC and LD
- Power Support 14/40

Coaxial Cable

HDC-CRYSTAL-GOLD



- 3+1 CCTV Full Copper Cable
- Single Strand Video Copper
- 36 Braiding
- Video Conductor Gauge: 0.024 Inches
- Length: 90 Meter Bundle
- Smart Box Packaging
- Heavy Copper
- A Grade PVC and LD
- Power Support 14/38

HDC-CAT-6 Indoor Cable



- Cat 6 Cable Full Copper
- Single Strand Conductor Gauge: 0.022 Inches (Pure Copper)
- 305m Cable Drum
- 4-pair UTP Cable
- 23 AWG Solid Copper for Superior Conductivity
- HDPE Insulation
- Heavy Gauge for Long Distance Coverage

HDC-CAT-6 Outdoor Cable



- Cat 6 Full Copper Cable
- Single Strand Conductor Gauge: 0.022 Inches (Pure Copper)
- 305m Cable Drum
- 4-pair UTP Cable
- 23 AWG Solid Copper for Superior Conductivity
- HDPE Insulation
- Single/Double Jacket

HDC-CRYSTAL 2 CORE POWER CABLE



- Cores Gauge 14/38
- Pure Copper, Multi-Strand
- 2 Core Power Cable 0.5mm
- Cable Length: 90 Meter

Coaxial Cable

HDC-RG6 CABLE DRUM



- Pure Copper
- Cable Length: 305 Meter
- 0.040 Inches Gauge Single Strand Video Copper with 64 braiding

HDC-RG59+2 CABLE



- Pure Copper Cable
- RG59 with 2 Core Power Cable
- Cable Length: 305 Meter
- 0.036 Inches Gauge Single Strand Video Copper with 64 braiding

LED TV's

32" Smart LED

HDC-32-80-SLIM



- Screen Size: 32 Inch (80cm)
- Resolution: 1366X768 (HDR)
- HDMI: 1
- USB: 2
- RAM: 1GB
- ROM: 8GB
- Earphone: 1
- Audio Output: 24W

40" Smart LED

HDC-40-100-SLT



- Screen Size: 40 Inch (102cm)
- Resolution: 1366X768 (HDR)
- HDMI: 1
- USB: 2
- RAM: 1GB
- ROM: 8GB
- Earphone: 1
- Audio Output: 24W

43" Smart LED

HDC-43-102-SLT



- Screen Size: 43 Inch (110cm)
- Resolution: 1366 X 768 (HDR)
- HDMI: 2
- USB: 2
- RAM: 1GB
- ROM: 8GB
- Earphone: 1
- Audio Output: 24W

50" Smart LED

HDC-50-125-SLT



- Screen Size: 50 Inch (125.7 cm)
- Resolution: 3840 X 2160 (HDR)
- HDMI: 2
- USB: 2
- RAM: 1GB
- ROM: 8GB
- Earphone: 1
- Audio Output: 24W

55" Smart LED

HDC-55-140-4K-SLT



- Screen Size: 55 Inch (140cm) Frameless
- Resolution: 3840 X 2160 (HDR)
- HDMI: 2
- USB: 2
- RAM: 1GB
- ROM: 8GB
- Earphone: 1
- Audio Output: 24W

65" Smart LED

HDC-65-165-4K-SLT



- Screen Size: 65 Inch (165cm)
- Resolution: 3840 X 2160 (HDR)
- HDMI: 2
- USB: 2
- RAM: 1GB
- ROM: 8GB
- Earphone: 1
- Audio Output: 24W



CCTV Routers

Mini Router

HDC-101



- SIM Based 4G Wi-Fi + LAN Device
- Support All SIM
- No Configuration Required
- Supports All CCTV DVRs, IP Cameras
- Biometric Devices (with Wi-Fi)

Double Antenna

HDC-102



- 80-100 MTR. Range
- Upto 16 Users
- RAM 512 MB
- Speed 150 Mbps
- IMEI Based
- IC Based (Think Well)
- Operating Temperature 10°C to 70°C

Tripple Antenna

HDC-103



- Triple Antenna
- 80-100 MTR. Range
- Multiple users
- RAM 512 MB
- Speed 150 Mbps
- IMEI Based
- IC Based (Think Well)

Orange Box Series

Dual Light Camera

CFL-2



- 3mp (2304*1296)
- Dual Light Sources (Automatic lights On on Human Detection)
- Monocular Dual Screen
- Support WiFi & Hotspot
- Two-Way Voice Intercom
- Accurate Humanoid Tracking
- Support 8-128g Memory Card
- Support Custom Setting Alarm Sound
- Support Standard ONVIF 2.4 Protocol

Bulb Camera

BUL-2



- 3mp (2304*1296)
- Dual Light Sources (Automatic lights On on Human Detection)
- Monocular Dual Screen
- Support WiFi & Hotspot
- Two-Way Voice Intercom
- Accurate Humanoid Tracking
- Support 8-128g Memory Card
- 110-230V AC Operating
- Support Standard ONVIF2.4 Protocol

Robot Camera

ROB-X



- Support Dual Lenses With Different Focal Lengths To Switch Freely
- Support WiFi & Hotspot Connection
- Two-Way Voice Intercom, Accurate Humanoid Tracking
- Support 8-128g Memory Card
- Support Custom Setting Alarm Sound
- Supports Simultaneous Four-Screen Viewing
- 5v1.5a Power Supply
- Supports Standard ONVIF Protocol

Dual Antenna Camera

ANT-2



- Single Light Source
- Support WiFi & Hotspot Connection
- Two-Way Voice Intercom, Accurate Humanoid Tracking
- Support 8-128g Memory Card
- Support Custom Setting Alarm Sound
- Supports Simultaneous Four-Screen Viewing
- 5v1.5a Power Supply
- Support for multi-user remote preview

Mini WiFi Camera

SUMO-2



- Single Light Source
- With USB port (expandable smart antenna, pairing with our door sensor, doorbell, etc.)
- Support WiFi & Hotspot Connection
- Two-Way Voice Intercom, Accurate Humanoid Tracking
- Support 8-128g Memory Card
- Support Custom Setting Alarm Sound
- Supports Simultaneous Four-Screen Viewing
- 5v1.5a Power Supply

PTX Camera

TAN-X



- Dual Lenses, Freely Switchable At Different Focal Length
- Dual Light Sources(4 White Light + 4 Infrared, Automatic lights On on Human Detection)
- Two-Way Voice Intercom
- 360-Degree Rotation
- Support 8 -128G Memory Card
- Support Online Purchase Of Cloud Storage
- Support Custom Setting Alarm Sound
- Supports Simultaneous Four-Screen Viewing
- Supports Standard ONVIF Protocol

Solar Camera

SLR-2



- Support Multi-User Remote Preview
- Support PIR Or APP Wake-Up
- Built-In Battery Power Supply
- Support Low Battery Sleep Protection Battery
- Support Solar Charging
- Support Dual Light Sources
- Support Humanoid Tracking
- Support Two-Way Voice Intercom
- Supports Standard ONVIF Protocol

Outdoor Bullet Camera

MTL-2



- Outdoor Waterproof Dual Light Source
- 9 White Light + Infrared Dual-Core Lights
- With Network Port
- Two-Way Voice Intercom
- Fixed Focal Length, Non-Rotatable
- Support 8-128G Memory Card
- Support Online Purchase Of Cloud Storage
- Support Custom Settings For Alarm Sound
- Support ONVIF Protocol



Wider Range of Safety Products



 facebook.com/hdcrystal

 www.hdcrystal.in

 sales@hdcrystal.in

