

5MP Starlight Dome IP (With PoE & Audio)



Model- HDC-IP-5MP-STL-ID-4K



Features:

- 1/3", 5 Megapixel CMOS Sensor
- Resolution: 2560(H) x 1440(V)
- Lens: 3.6mm (Fixed)
- Maximum 25/30 fps
- Support LAN Wire
- Up to 20 to 25m IR Distance, Array Smart LEDs
- H.264/H.265/H.265+ Encoding Format
- 24/7 Full Color Vision
- Built-in Mic
- 3D DNR, AGC, AWB, BLC Supported
- Metal+Fiber Body

| | |
|--------------------|---|
| Product Name | 5MP Starlight Dome IP |
| Image Sensor | 1/3", 5MP CMOS Sensor |
| D/N | Support D/N Switching (IR-CUT Optional) |
| Shutter | 1/25-1/10000 |
| White Balance | Support Automatic White Balance |
| WLC | Support |
| Noise Reduction | Support 3D-DNR |
| Night Color Vision | Starlight Illumination CMOS Sensor, Color 0.0001Lux@F1.2 |
| WDR | Support D-WDR |
| Motion Detection | Support |
| Privacy Shelter | Support 4 Areas |
| Mirror | Support |
| OSD | Support OSD Setting, Drag the Position freely |

| | |
|---------------------|--|
| Compression | H.265+/H.265 |
| Resolution | Main Stream:5MP 2592*1944, Sub Stream:448P(800*448) |
| Frame Rate | 25ps(50HZ), 25fps(60HZ) |
| Ethernet | RJ-45 10M/100M |
| Network Protocol | HTTP, TCP/IP, IPv4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, IP Search (Support P6S IP Camera, DVR, NVR and etc.) |
| Access Protocol | Support ONVIF, P6S, Private Protocol/CGI |
| Client | IOS, Android, Ipad, Windows |
| Audio | G.711U |
| Input | 1Ch |
| Power | Poe Support, DC 12volt |
| Working Temperature | -10°C ~ + 55°C |
| Working Humidity | 10% ~ 95% RH (non-condensing) |