

4MP Starlight Bullet IP (2 Way Audio with PoE)



Model- HDC-IPC-4MP-AUDI-OD-3D



Features:

- 1/3", 4 Megapixel CMOS Sensor
- Resolution: 2560(H) x 1440(V)
- Lens: 3.6mm (Fixed)/ 6mm (Optional)
- Maximum 25/30 fps
- Support LAN Wire
- Up to 25 to 30m IR Distance, Array Smart LEDs
- H.264/H.265/H.265+ Encoding Format
- 2 Way Communication through NVR
- Alarm Alert on Motion Detection
- 24/7 Full Color Vision
- Built-in Mic
- 3D DNR, AGC, AWB, BLC Supported
- Metal Body, IP66 Weatherproof

Product Name	4MP Starlight Bullet IP
Image Sensor	1/3", 4MP CMOS Sensor
D/N	Support D/N Switching (IR-CUT Optional)
Shutter	1/25-1/10000
White Balance	Support Automatic White Balance
WLC	Support
Noise Reduction	Support 3D-DNR
WDR	Support D-WDR
Night Color Vision	Support
Motion Detection	Starlight Illumination CMOS Sensor, Color 0.0001Lux@F1.2
Privacy Shelter	Support 4 Areas
Mirror	Support
OSD	Support OSD Setting, Drag the Position freely

Compression	H.264/H.265/H.265+
Resolution	Main Stream:4.0MP(2560*1440), Sub Stream:448P(800*448)
Frame Rate	25ps(50HZ), 25fps(60HZ)
Ethernet	RJ-45 10M/100M
Network Protocol	HTTP, TCP/IP, IPv4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, IP Search (Support P6S IP Camera, DVR, NVR and etc.)
Access Protocol	Support ONVIF, P6S, Private Protocol/CGI
Client	IOS, Android, Ipad, Windows
Audio	G.711U
Input	1 Ch
Output	1Ch
Power	Poe Support, DC 12volt
Working Temperature	-10°C ~ + 55°C
Working Humidity	10% ~ 95% RH (non-condensing)