


64 Channel NVR Audi Series



Model- HDC-NVR-64CH-AUDI-9HDD-AUDI-4K-H265-2D



Introduction:

H.265+ 64 CH IVR, support 64 CH 4K IP camera input and output, support smart analysis IPC, 1 CH 4K/4CH 1080P/16 CH sub-code stream playback, 9 pcs HDD (max 10TB), 1CH VGA, 1 CH HDMI, support to upgrade IPC remote, modify IP camera address and light board parameters, support alarm and audio, support mobile view.

Features:

- Mode 1: Support 36 Channels IPC input (8MP/D1+36 CH Preview+16CH playback)
- Mode 2: Support 64 Channels IPC input (8MP/D1+36 CH Preview+16CH playback)
- Support H265,H264,H265+ compression format
- Support synchronized recording, remote view, backup recording in MP4 format, mobile view
- Support VGA/HDMI
- Support preview image and playback image electronic amplification
- Support RTSP, GB28181, ONVIF protocol
- Support HTTP, RTMP
- Support alarm capture, send alarm information by email
- Support DDNS,UPNP,NTP,P2P...etc.
- Support WEB, mobile view, IMS surveillance
- Support IPC smart analysis: target count, E-fence, line crossing, absent alarm, E-bike detection
- Support channel tour round grouping
- Support network inspection-network traffic monitor, ether-detect packet, network diagnosis...etc.
- Support max 4CH 1080P playback and 16CH sub-code playback
- Support HTML5 remote login operation
- Support to add IPC manually or automatically in LAN
- Support to upgrade IPC online and by memory
- Support to maintain IPC under private protocol, including restore, restart, enable or disable all network function
- Support disconnected network supplement function, optimize bandwidth incoming up to 512M

PARAMETERS	
Chipset	RK3568
OS	Embedded Linux System
Bandwidth	512M
Video Format	H.265+/H.265/H.264
Record Resolution	4K/1080P/720P/D1
Smart Function	Target Count, Human Detect, E-Fence, Line-Crossing, Retrograde Alarm, Absent Alarm... etc.
Recording Method	Manual, Schedule, Motion Detection, Timing, Alarm, Stop
Playback	1CH 4K, 4 CH 1080P(1920*1080), 16Ch D1
Playback Mode	Regular Playback, Event Playback
Backup Mode	USB Device/ Network
Video Input	Support to Connect 36 CH IPC (8MP/D1+36 CH preview+16 CH playback) Support to connect 64 CH IPC (8MP/D1+36 CH preview+16 CH playback)

Video									
Normal Mode	36 CH Normal IPC								
Split	1	4	6	8	9	16	25	36	
Decode	4K	4*108 OP	5MP+5* D1	3MP+7* D1	D1				
Normal Mode	64 CH Normal IPC								
Split	1	4	6	8	9	16	25	36	64
Decode	4K	4*108 OP	5MP+5* D1	3MP+7* D1	D1				
Storage									
HDD					9 SATA				
HDD Capacity					10TB				
Storage					Local HDD				
Backup Mode					USB Portable HDD, Memory				

External Connection	
Audio Intercom	1 pcs 3.5mm TRS port
Audio Output	1 pcs 3.5mm TRS port
Network Port	2 pcs, RJ45 1000M Ethernet port
Series Port	RS-485 port
USB port	2 pcs USB2.0
Alarm Input	2 CH
Alarm Output	1 CH
General	
Power Supply	AC100-240V 200W
Power Consumption	≤160W
Working Temperature	-10°C ~ 55°C/
Working Humidity	10%-90%
Size	Device : 440X430X90mm, package: 545X535X225mm
Weight/Pcs	Net weight: 9Kg, Gross weight:9.8Kg (without HDD)
Package	2 pcs/CTN,570*570*490mm , weight 20.2KG